



Product Name: RS232 to RS485/RS422 Converter

Product Type: ATC-104

Features:

- Converts RS232 to RS485/RS422
- Data transmission rates up to 115.2K bps
- Transmission distance up to 4000 ft (1250 meters)
- User selectable by switch for HALF/FULL DUPLEX
- Auto switch the HALF DUPLEX TX without extra I/O control
- With LED indicator for transmission and receiving
- Easy to install with screw terminal connector
- Termination (120 Ohm) resistor is selectable by switch
- Built in transient voltage suppressor against the thunder
- Built in optical couple isolator (Option device)

Specifications:

Dimension:	ATC-104 75 (W) X 120 (L) X 25 (H) mm
Power:	9V ~ +12VDC 300mA (minmum)
Operation Temperature:	0 ° C ~ 65 ° C
Humidity:	20% ~ 95% RH

Ordering Information:

重要!	讀取卡片種類	通訊介面	顯示幕文字
訂購規格視各機種類別不同， 可能有所變動，如需進一步， 確定，請與業務人員洽詢！	E=EM	T=TCP/IP	E=英文字
	N=TEMIC鎖碼	R=RS232 RS485 RS422	C=中文字
	M=Mifare	---	---
	T=TI	---	---
	H=HID	---	---
	F=Felica	---	---

- 型號標準為：型號-讀取卡片種類(E/N/M/T/H/F)-通訊介面(T/R)-顯示幕文字(E/C)
 - 讀取卡片種類為：E=EM，N=TEMIC鎖碼，M=Mifare，T=TI，H=HID，F=Felica
 - 通訊介面為：T=TCP/IP，R=RS232, RS485, RS422
 - 顯示幕文字為：E=英文字，C=中文字
 - 例：如訂購 PR-80C TCP/IP介面的Mifare中文顯示讀卡機，則訂貨型號註明：PR-80C-M-T-C
-

Reference models:

Taiwan Jantek Electronics., Ltd.
 Add:6F-1, No. 1, Wuquan 1St.Rd.,Xinzhuang District, TEL : 886-2-22991255
 New Taipei City 24892,Taiwan, R.O.C.
 FAX : 02-2299-1257 / 02-2299-7412

www.jantek.com.tw
 TEL : 886-2-22991255

Email : service@jantek.com.tw