

Product Name: TCPIP Module

Product Type: JTM-300

Features:

Specifications:

specifications	
CPU :	16 bit CPU, 100MHz
Memory :	512KB FLASH, 32KB RAM
Connector Type :	JTC-300 : DB9 (Male) / RJ-45
Watch Dog :	Support watch Dog, system never hang
Interface	
Ethernet :	Support full duplex / half duplex Support twisted pair crossover detection and auto-correction (Auto-MDIX)
Serial :	JTM-300 : TTL JTC-300 : RS-232/485/422, half/full duplex
No. of serial Port :	1
Signals :	RS-232:TxD, RxD, RTS, CTS, GND RS-485 2 wire: A+/B- RS-422 4 wire: T+/T-, R+/R-
Baud rate :	1200 bps~921.6kbps
set up	
Parity Check :	None, even, odd
Data bits :	5, 6, 7, 8
Stop bits :	1, 1.5, 2
Flow Control :	RTS/CTS
OS : Windows XP, Windows 2000, Windows NT, Windows95/98 ME, Vista, Windows 7, Windows 10 . . .	
Power requirements :	
JTM-300 : DC5V, Max.300mA JTC-300 : DC9V~24V, Max.600mA	
Operating temperature : 0-70	
humidity : 5 - 95%RH	
temperature : -20-85	

Size : 65 x 26 x 7 mm (W x L x H)
Support : TCP, IP, UDP, ARP, DHCP, ICMP, HTTP

Ordering Information:

Reference models:

JTM-200TCPIP Module

Taiwan Jantek Electronics., Ltd.

www.jantek.com.tw

Add:6F-1, No. 1, Wuquan 1St.Rd.,Xinzhuang District, TEL : 886-2-22991255

New Taipei City 24892, Taiwan, R.O.C.

FAX : 02-2299-1257 / 02-2299-7412

Email : service@jantek.com.tw